



BALE SPEARS

AB21 | AB31 | AB32 | AB42 | AB43



SPECIFICATIONS

- Offering optimal rigidity and capacity, these John Deere bale spears are built for a long working life and designed for the loading, carrying, and stacking of baled organic materials typically used for livestock feed and bedding in agricultural applications.
- Low-profile design provides unrestricted visibility to the bale spear and tine tips.
- Round bale spears are replaceable and come in three different configurations of single, dual, or triple to help match numerous bale-handling applications.
- Round bale tines are retained with cross-bolts, making them easy to replace.
- Quick-Tatch™ mounting provides quick and easy hookup and removal.
- These bale spears are compatible with all skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs) equipped with a skid steer-style Quik-Tatch coupler.

| | AB21 | AB31 | AB32 | AB42 | AB43 |
|---------------------------------|--|--|--|--|--|
| Description | <i>Single Bale</i> | <i>Single Bale, Heavy Duty</i> | <i>Dual Bale</i> | <i>Dual Bale, Heavy Duty</i> | <i>Triple Bale</i> |
| Capacity* at Load Center | 907 kg (2,000 lb.) at 0.61 m (24 in.) | 1361 kg (3,000 lb.) at 0.61 m (24 in.) | 1361 kg (3,000 lb.) at 0.61 m (24 in.) | 1814 kg (4,000 lb.) at 0.61 m (24 in.) | 1814 kg (4,000 lb.) at 0.61 m (24 in.) |
| Width | 1.15 m (45.25 in.) | 1.24 m (48.75 in.) | 1.15 m (45.25 in.) | 1.24 m (48.75 in.) | 1.42 m (56.00 in.) |
| Height | 0.57 m (22.38 in.) | 0.64 m (25.00 in.) | 0.59 m (23.13 in.) | 0.64 m (25.00 in.) | 0.62 m (24.25 in.) |
| Length | 1.28 m (50.50 in.) | 1.42 m (55.75 in.) | 1.28 m (50.50 in.) | 1.42 m (55.75 in.) | 1.33 m (52.25 in.) |
| Spear Length | 1.24 m (49.00 in.) | 1.35 m (53.00 in.) | 1.24 m (49.00 in.) | 1.35 m (53.00 in.) | 1.24 m (49.00 in.) |
| Weight | 66 kg (145 lb.) | 91 kg (200 lb.) | 70 kg (155 lb.) | 109 kg (240 lb.) | 102 kg (225 lb.) |
| Vehicle Compatibility | 316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs; 204L†, 244L†, 304L†, and 324L† CWLs | | | | |

*Bale-spear capacity. See Operator's Manual for machine capacity. / †Requires skid-steer-style Quik-Tatch coupler for operation.