



DOZER BLADES

DB84 | DB96



SPECIFICATIONS

- Add a John Deere dozer blade to turn your skid steer loader (SSL) or compact track loader (CTL) into a compact bulldozer.
- There's nothing light duty about these dozer blades. Their rugged design delivers maximum uptime to a wide variety of tasks — from stripping clay to finish grading.
- Quik-Tatch™-mounted blade comes standard equipped with reversible cutting edge and skid shoes for long-term durability.
- Power-angle-tilt lets you make blade adjustments on the go, for increased versatility and maximum productivity.
- These dozer blades are optimized to work with John Deere SSLs and CTLs. They are also compatible with many competitive models.

	DB84	DB96
Weight	703 kg (1,550 lb.)	737 kg (1,625 lb.)
Overall Width	2133 mm (84 in.)	2438 mm (96 in.)
Length	800 mm (31.5 in.)	800 mm (31.5 in.)
Blade Height	610 mm (24 in.)	610 mm (24 in.)
Blade Width (full angle)	1882 mm (74.1 in.)	2151 mm (84.7 in.)
Cutting Edge (reversible)	16 x 153 mm (0.625 x 6 in.)	16 x 153 mm (0.625 x 6 in.)
Degree of Angle	30, right or left	30, right or left
Degree of Tilt	10, up or down	10, up or down
Connection		
Hydraulic	12.7-mm (0.5 in.) quick-connect couplers	12.7-mm (0.5 in.) quick-connect couplers
Electric	3 pin	3 pin
Adjustable Skid Shoe	Standard	Standard
Vehicle Compatibility	318G, 320G, and 324G SSLs; 317G and 325G CTLs	330G and 332G SSLs; 331G and 333G CTLs