

# PALLET FORKS

P45 | P60 | SEVERE DUTY



## SPECIFICATIONS

- Pallet forks are available in lengths of 42, 48, and 60 inches (check specifications below for compatibility).
- Skid-resistant steps on both sides of the pallet-fork frame ease vehicle entrance and exit.
- Single-piece backrest is available on P45 and P60 options. Severe-duty skid steer loader option includes a walk-through backrest with a bolt-on option.
- Severe-duty pallet forks offer increased capacity and durability over the previous fork-frame design.
- Brick-guard design provides strength and smooth surfaces, for protection against load damage.
- Design enables excellent visibility, and P45 and P60 standard frames include load-securing “D” ring.
- Quik-Tatch™ system allows easy attachment hook-up in seconds.
- These pallet forks are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They are compatible with most competitive models.

|                                                       |                                                      |                                                                               |                                                                  |                                                                  | SEVERE DUTY                         |                                        |                                        |
|-------------------------------------------------------|------------------------------------------------------|-------------------------------------------------------------------------------|------------------------------------------------------------------|------------------------------------------------------------------|-------------------------------------|----------------------------------------|----------------------------------------|
| Machine                                               | SSLs / CTLs                                          |                                                                               |                                                                  | SSLs / CTLs                                                      | CWLs                                | SSLs / CTLs                            |                                        |
| Model                                                 | P45                                                  |                                                                               |                                                                  | P60                                                              |                                     | PF45                                   | PF60                                   |
| Fork Tine Load Rating at 600-mm (24 in.) Load Center* | 1700 kg (3,750 lb.)                                  | 2500 kg (5,500 lb.)                                                           | 2820 kg (6,200 lb.)                                              | 2820 kg (6,200 lb.)                                              | 4000 kg (8,800 lb.)                 | 4000 kg (8,800 lb.)                    | 4000 kg (8,800 lb.)                    |
| Frame Width                                           | 1410 mm (55 in.)                                     | 1410 mm (55 in.)                                                              | 1410 mm (55 in.)                                                 | 1770 mm (70 in.)                                                 | 1520 mm (60 in.)                    | 1380 mm (54 in.)                       | 1730 mm (68 in.)                       |
| Frame Height                                          | 990 mm (39 in.)                                      | 990 mm (39 in.)                                                               | 990 mm (39 in.)                                                  | 990 mm (39 in.)                                                  | 535 mm (21.1 in.)                   | 940 mm (37 in.)                        | 940 mm (37 in.)                        |
| Overall Weight (frame and 2 tines)                    |                                                      |                                                                               |                                                                  |                                                                  |                                     |                                        |                                        |
| 1065 mm (42 in.)                                      | 181 kg (397 lb.)                                     | 187 kg (412 lb.)                                                              | N/A                                                              | N/A                                                              | N/A                                 | N/A                                    | N/A                                    |
| 1220 mm (48 in.)                                      | 189 kg (416 lb.)                                     | 198 kg (435 lb.)                                                              | 198 kg (435 lb.)                                                 | 209 kg (459 lb.)                                                 | 342 kg (754 lb.)                    | 331 kg (729 lb.)                       | 359 kg (790 lb.)                       |
| 1520 mm (60 in.)                                      | N/A                                                  | N/A                                                                           | N/A                                                              | N/A                                                              | 370 kg (816 lb.)                    | 360 kg (793 lb.)                       | 388 kg (854 lb.)                       |
| Overall Length (frame and 2 tines)                    |                                                      |                                                                               |                                                                  |                                                                  |                                     |                                        |                                        |
| 1065 mm (42 in.)                                      | 1310 mm (52 in.)                                     | 1310 mm (52 in.)                                                              | N/A                                                              | N/A                                                              | N/A                                 | N/A                                    | N/A                                    |
| 1220 mm (48 in.)                                      | 1470 mm (58 in.)                                     | 1470 mm (58 in.)                                                              | 1470 mm (58 in.)                                                 | 1470 mm (58 in.)                                                 | 1445 mm (56.9 in.)                  | 1520 mm (60 in.)                       | 1520 mm (60 in.)                       |
| 1520 mm (60 in.)                                      | N/A                                                  | N/A                                                                           | N/A                                                              | N/A                                                              | 1750 mm (68.9 in.)                  | 1830 mm (72 in.)                       | 1830 mm (72 in.)                       |
| Fork Thickness                                        | 36 mm (1.4 in.)                                      | 40 mm (1.6 in.)                                                               | 45 mm (1.8 in.)                                                  | 45 mm (1.8 in.)                                                  | 50 mm (2 in.)                       | 50 mm (2 in.)                          | 50 mm (2 in.)                          |
| Fork Spacing                                          | 102 mm (4 in.)                                       | 102 mm (4 in.)                                                                | 102 mm (4 in.)                                                   | 102 mm (4 in.)                                                   | 136 mm (5.35 in.)                   | 127 mm (5 in.)                         | 136 mm (5.35 in.)                      |
| Vehicle Compatibility                                 | 316GR, 318G, 320G, and 324G SSLs; 317G and 325G CTLs | 316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs | 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs | 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs | 204L†, 244L†, 304L†, and 324L† CWLs | 330G and 332G SSLs; 331G and 333G CTLs | 330G and 332G SSLs; 331G and 333G CTLs |

\*Pallet-fork capacity listed. Reference machine Operator's Manual for machine capacity.

†Requires skid-steer-style Quik-Tatch coupler for operation.

