

ROLLOUT BUCKETS

RB72 | RB84 | RB96



SPECIFICATIONS

- Quality-manufactured John Deere rollout buckets feature an open design that enables quick, clean, and easy material loading.
- Available in a range of three sizes, rollout buckets are ideal for achieving elevated dump heights in high-capacity applications, including construction, forestry, agriculture, demolition, recycling, and land management.
- Each model comes standard with a universal bolt-on cutting edge that is double beveled and reversible, for extended wear life.
- Industrial-strength, high-pressure cylinders are cushioned for smooth bucket operation and are constructed with induction-hardened, double chrome-plated rods, for maximum durability.
- These rollout buckets are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They're also compatible with many competitive models.

	RB72	RB84	RB96
Weight	532 kg (1,170 lb.)	580 kg (1,275 lb.)	618 kg (1,360 lb.)
Width	1850 mm (73 in.)	2150 mm (84.75 in.)	2480 mm (97.5 in.)
Height	820 mm (32.3 in.)	820 mm (32.3 in.)	820 mm (32.3 in.)
Length	1270 mm (50 in.)	1270 mm (50 in.)	1270 mm (50 in.)
Heaped Capacity	0.91 m ³ (1.19 cu. yd.)	1.10 m ³ (1.44 cu. yd.)	1.28 m ³ (1.68 cu. yd.)
Dump			
Reach	860 mm (34 in.)	860 mm (34 in.)	860 mm (34 in.)
Angle	114 deg.	114 deg.	114 deg.
Hydraulic Cylinder			
Pivot Pin Diameter	38 mm (1.5 in.)	38 mm (1.5 in.)	38 mm (1.5 in.)
Bore Diameter	64 mm (2.5 in.)	64 mm (2.5 in.)	64 mm (2.5 in.)
Rod Diameter	38 mm (1.5 in.)	38 mm (1.5 in.)	38 mm (1.5 in.)
Maximum Operating Pressure	25 000 kPa (3,625 psi)	25 000 kPa (3,625 psi)	25 000 kPa (3,625 psi)
Bolt-On Cutting Edge			
Length	200 mm (8.0 in.)	200 mm (8.0 in.)	200 mm (8.0 in.)
Thickness	19 mm (0.75 in.)	19 mm (0.75 in.)	19 mm (0.75 in.)
Vehicle Compatibility	316GR, 318G, 320G, and 324G SSLs; 317G and 325G CTLs	320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs	330G and 332G SSLs; 331G and 333G CTLs; 204L*, 244L*, 304L*, and 324L* CWLs

*Requires skid-steer-style Quik-Tatch™ coupler for operation.

