



# VIBRATORY ROLLERS

VR66C | VR73C | VR84C



## SPECIFICATIONS

- John Deere vibratory rollers turn a skid steer loader (SSL), compact track loader (CTL), or compact wheel loader (CWL) into a powerful compactor. Ideal for asphalt patch, foundation, trench, and flatwork compaction, they're very economical since owning one eliminates the costs and maintenance of a self-propelled roller.
- Bidirectional operation increases productivity.
- Powered by standard hydraulics, vibratory rollers produce compaction forces up to 9,370 lbf.
- With drum oscillation of  $\pm 15$  degrees, these attachments are easy to maneuver.
- Quik-Tatch™ compatible, they take only one minute to hook up.
- Drum and shaft bearings are lubricated and cooled in oil bath for long life.
- These vibratory rollers are optimized to work with Deere SSLs, CTLs, and CWLs. They are also compatible with many competitive models.

	VR66C	VR73C	VR84C
<b>Overall Width</b>	1.8 m (72 in.)	2.0 m (79 in.)	2.3 m (90 in.)
<b>Overall Length</b>	99 cm (39 in.)	99 cm (39 in.)	99 cm (39 in.)
<b>Overall Height</b>	79 cm (31 in.)	79 cm (31 in.)	79 cm (31 in.)
<b>Drum Width</b>	1.7 m (66 in.)	1.8 m (73 in.)	2.1 m (84 in.)
<b>Drum Diameter</b>			
Smooth	61 cm (24 in.)	61 cm (24 in.)	61 cm (24 in.)
Sheepsfoot (without pads)	51 cm (20 in.)	51 cm (20 in.)	N/A
<b>Drum Oscillation</b>	$\pm 15$ deg.	$\pm 15$ deg.	$\pm 15$ deg.
<b>Dynamic Force</b>	3538 kg (7,800 lbf)	3878 kg (8,550 lbf)	4250 kg (9,370 lbf)
<b>Vibrations per Minute</b>			
Range	41–95 L/min. (11–25 gpm)	41–95 L/min. (11–25 gpm)	41–95 L/min. (11–25 gpm)
Optimum Performance	75.7 L/min. (20 gpm)	75.7 L/min. (20 gpm)	75.7 L/min. (20 gpm)
<b>Operating Weight</b>			
Smooth Drum	975 kg (2,150 lb.)	1043 kg (2,300 lb.)	1148 kg (2,530 lb.)
Sheepsfoot Drum	945 kg (2,085 lb.)	1012 kg (2,230 lb.)	N/A
<b>Vehicle Compatibility</b>			
Smooth Drum	316GR <sup>†</sup> , 318G <sup>†</sup> , 320G <sup>†</sup> , 324G <sup>†</sup> , 330G, and 332G SSLs; 317G <sup>†</sup> , 325G, 331G, and 333G CTLs	330G and 332G SSLs; 317G <sup>†</sup> , 325G, 331G, and 333G CTLs	330G and 332G SSLs; 325G, 331G, and 333G CTLs; 244L* and 324L* CWLs
Sheepsfoot Drum	316GR <sup>†</sup> , 318G <sup>†</sup> , 320G <sup>†</sup> , 324G <sup>†</sup> , 330G, and 332G SSLs; 317G <sup>†</sup> , 325G, 331G, and 333G CTLs	330G and 332G SSLs; 317G <sup>†</sup> , 325G, 331G, and 333G CTLs	N/A

\*Requires skid-steer-style Quik-Tatch coupler for operation. / <sup>†</sup>Requires additional weights.